



Model VISION E01	VISION E6501	VISION E7501	VISION E8601
Display			
Size	65	75	86
Type	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD
Aspect Ratio	16:09	16:09	16:09
Backlight	LED	LED	LED
Resolution	3840×2160	3840×2160	3840×2160
Refresh Rate	60Hz	60Hz	60Hz
Brightness	450 nits	500 nits	500 nits
Contrast Ratio	4000:1	4000:1	4000:1
Viewing Angle	178°	178°	178°
Colors	1.07B(10 bits)	1.07B(10 bits)	1.07B(10 bits)
Life(MTBF)	≥120,000H	≥120,000H	≥120,000H
Touch Area(L*W)/mm	1452*836	1689*970	1932*1108
Display Area(L*W)/mm	1428.48*803.52	1650.24*928.26	1895.4*1065.9
Glass Material	AG(anti-glare) tempered glass	AG(anti-glare) tempered glass	AG(anti-glare) tempered glass
Glass Thickness	4mm	4mm	4mm
Glass Hardness	Mohs 7	Mohs 7	Mohs 7
Speaker	20W*2	20W*2	20W*2
Power /	AC:100-240V;60/50Hz;69W(Eco); ≤0.5W(Standby)	AC:100-240V;60/50Hz; 110W(Eco);≤0.5W(Standby)	AC:100-240V;60/50Hz; 165W(Eco); ≤0.5W(Standby)
Android			
Version	Android 11	Android 11	Android 11

CPU	Amlogic T982, Cortex A55*4 1.9GHz	Amlogic T982, Cortex A55*4 1.9GHz	Amlogic T982, Cortex A55*4 1.9GHz
GPU	MaliG52 MP2	MaliG52 MP2	MaliG52 MP2
RAM	4G DDR4	4G DDR4	4G DDR4
ROM	32G	32G	32G
WiFi	IEEE 802.11a/b/g/n/ac (2.4GHz+5GHz)	IEEE 802.11a/b/g/n/ac (2.4GHz+5GHz)	IEEE 802.11a/b/g/n/ac (2.4GHz+5GHz)

Connection

Konektori na prednjoj strani

HDMI 2.0 in*1(CEC&ARC)
 USB Type-C 3.0*1(USB+Video+Audio+15W Charge: 5V/3A, optional 65W)
 USB Type-C 3.0*1(USB+Video+Audio+15W Charge: 5V/3A, optional 65W)
 USB Type-C 3.0*1(USB+Video+Audio+15W Charge: 5V/3A, optional 65W)
 USB-A 3.0*3(2.0 in android, 3.0 in OPS)
 Touch USB-B 2.0 for HDMI*1
 DP 1.2 in*1

Konektori na zadnjoj strani

HDMI 2.0 in*2(CEC)
 VGA in(DB9)*1
 VGA Audio in(3.5mm)*1
 AV in(RCA)*1
 YPbPr in(RCA)*1
 Mic in(3.5mm) 8m*6
 HDMI 2.0 out*1
 AV out(RCA)*1
 Headphone out(3.5mm)*1
 Android USB-A 3.0*1
 Android USB-A 2.0*1
 Touch USB-B 2.0*1
 RJ45*2(100Mbps in Android, 1000Mbps in OPS, shared ethernet)
 WiFi antenna*3
 BT 5.1 antenna*1
 TF Card*1
 RS232*1

Touch

Touch Performance Technology:Infrared; Minimum Touch Object:≥2.5mm; Touch Precision:1mm; Positioning Precisor
 Touch Durability ≥60,000,000 times.(More than 100,000 hours)

Touch Points 40-point touch, 20-point writing
Touch Tools Fingers, pens, or other untransparent objects.
Response Time Single touch:<5ms, Dual touch:<7ms.
Light Resistance Work normally under 80,000 lux illumination(Full daylight ≈ 100,000 lux)
OS Compatibility Windows XP/7/8/10; Linux; Chrome OS; Mac OS; Android
Touch Features Driver-free, calibration-free, waterproof, dustproof, ultra-thin, light.
Power Supply <2W, DC 5V±5%, electric current<500mA.

DIMENZIJE I TEŽINA

Dimenzije cm	1488*928*100	1733*1070*94.7	1968*1201*97
Dimenzije kutije cm	1690*210*1060	1920*210*1150	2154*230*1354
Težina neto kg	45	57	78
Težina bruto kg	57	71	102